



Model	Outlet	Inlet
PH 1001	2 x 2 – ½” Male Vee thread fitted with blank cap and chain.	4” Table E BS 10 Flange



Model	Outlet	Inlet
PH 1002	2 x 2-½” BS336 instantaneous female Coupling	4” Table E BS 10 Flange



Model	Outlet	Inlet
PH 1004	2 x 2 – ½” pressure regulating valve with female BS336 instantaneous outlet	4” Table E BS 10 Flange

Multron Systems Pte Ltd

217 Kallang Bahru, Multron Building, Singapore 339 347

☎ 6395 6868

✉ info @ multron.com

📠 6395 6869

🌐 www. multron. com





3-Way Pillar Hydrant

Model PH-1003-1 & PH1003-2 can be fitted with an underground 6" Gate Valve with Spindle Cap (Sluice Valve) and operated by using a Hydrant key and Bar.

Body Material : Cast Iron to BS 1452
 Outlet : Copper Alloy to BS 1400
 Test Pressure : 20 Bar (300 psi)
 Working Pressure : 10 Bar (150 psi)
 Finishing : Red

Model	Outlet	Inlet
PH1003-1	2 X (2-1/2") Male Thread 1 X 4" Male Thread	6" Table E BS 10 Flange
PH1003-2	2 X (2-1/2") Screwed Oblique Landing Valve with Female Instantaneous Outlet BS336 1 X 4" Male Thread	6" Table E BS 10 Flange



Model :PH1003-1 Model : PH1003-2



2-Way Pillar Hydrant with Monitor

Body : Cast Iron
 Valve Seal : Nylon
 Valve Seal Ring : Bronze
 Test Pressure : 20 Bar (300 psi)
 Working Pressure : 10 Bar (150 psi)

Model No.	Outlets	Inlet
PH1005M	2 x (2 - 1/2") oblique landing valve with female instantaneous outlet, 1 x (4") monitor unit	4" PN 16 BS 4504

Model : PH1005M

Multron Systems Pte Ltd

217 Kallang Bahru, Multron Building, Singapore 339 347

6395 6868
6395 6869

info @ multron.com
www. multron. com

